HP Latex R1000 Printer



Help grow your business with easy, automatic printing of high-value rigid jobs, and white¹





Get amazing colors for rigid jobs up to 64 inches

- Grow your business into higher value rigid jobs with vibrant HP Latex gamut, preserving media look and feel
- Gain versatility with HP Latex Ink—from indoor/outdoor signage to thermoforming and high-quality decoration.
- Win more jobs with UL ECOLOGO® Certified. water-based HP Latex Inks that produce odorless

We've removed the barriers to print with white1

- Be creative on a wide range of applications with glossiest white that resists yellowing over time.
- No waste between white jobs³ with removable HP Thermal Inkjet printheads stored in offline rotating chamber.
- You're always ready to print white—automatic recirculation and printhead cleaning eliminate manual purging.

Manage your peaks in-house with smart printing

- Get high-speed quality in all print modes—print up to 15 outdoor bds/hr with belt system and smart vacuum.4
- · Help avoid costly operating mistakes with an easy interface, including assisted loading and advanced queuing.
- Maximize uptime with automatic maintenance and smart service tools for fast diagnosis and issue resolution.
- Keep your operators always up-to-date with HP PrintOS continuous online training.

For more information, please visit http://www.hp.com/go/LatexRseries

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://hplatexknowledgecenter.com/

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

¹ Glossiest white based on internal HP testing in January, 2018 compared to the HP Scitex FB750/FB550 Printer using UV-curable ink technology. White ink measured for the level of gloss at 60 degrees on a rigid material (acrylic). Tested using Glossmeter BYK micro-TRI-gloss (20°, 60°, 85°), compatible with ISO 2813 and ASTM D523 relative to glossiness measure. High opacity and resists yellowing over time based on internal HP WeatherOmeter testing October, 2017 with 1 dot-per-pixel HP Latex Overcoat, on a range of rigid and flexible unlaminated substrates. Yellowing based on L* and B* of white underflood samples.

² HP Latex Inks are UL ECOLOGO® Certificed. UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental

considerations (see http://www.ul.com/EL). There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

3 When HP 886 White Latex Printheads are placed in the storage cassettes, no white ink is used for servicing when printheads are not in use.

4 Outdoor mode 3-pass, 70%. On 4 x 8 ft (1.2 x 2.4 m) boards.

Technical specifications

Print

PIIIIL	
Printing modes	15 m²/hr - Indoor High Quality (12p 120%) 28 m²/hr - Indoor Production (6p 110%) 56 m²/hr - Outdoor (3p 70%) 25 m²/hr - White Spot (100%) 11 m²/hr - White Overflood (100%) 3.6 m²/hr - 3 layers day & night¹
Print resolution	Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex Inks
Ink cartridges	9 (cyan, magenta, yellow, black, light cyan, light magenta, HP Latex Optimizer, HP Latex Overcoat, white)
Cartridge size	3L
Printheads	8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 HP Latex Optimizer, 2 white)
Long-term print-to-print repeatability	Average ≤ 1.0 dE2000, 95% of colors ≤ 2 dE2000 ²
Media	
Handling	Flatbed, sheet feed, vacuum belt media drive for easy loading and accurate media advance
Media types	Rigid substrates: paper foamboard, plastic foamboard, PVC foam, plastic corrugated, acrylic, polycarbonate, polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates ³ : PVC banner, self-adhesive vinyl, coated paper, polypropylene, polystyrene, polycarbonate, polyester, textile (non porous), canvas, leather
Rigid media size	297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of optional extension tables)
Thickness	Up to 50.8 mm
Applications	Signage: indoor, flat, backlit, thermoformed; Decoration: wall coverings, window decoration; Vehicle decoration: fleet graphics, wraps, decals; Textile: soft signage, frontlit, backlit; POS and Packaging: corrugated displays, short-run customized packaging, prototyping
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T)
Dimensions (w x d x	h)
Printer	4.21 x 2.04 x 1.75 m (printer); 4.21 x 3.64 x 1.75 m (including standard input and output tables)
Shipping	4.43 x 2.24 x 2.15 m
Operating area	6.61 x 6.03 x 3 m
Weight	
Printer	1275 kg
Shipping	2275 kg
What's in the box	HP Latex R1000 Printer; HP Latex R Series White Upgrade Accessory Kit; HP 886 Latex Printheads; HP Latex Printhead Cleaning Kit; standard input and output tables; foot switch; HP Internal Print Server and displays (x2); printer maintenance kit; warranty and intro docs
Environmental rang	es
Operating temperature	15 to 30⁰C
Operating humidity	20 to 70% RH (non-condensing)
Power	
Consumption	8 to 10 kW (typical)
Certification	
Safety	IEC 60950-1+A1+A2 compliant; United States and Canada (CSA listed); EU (LVD and MD compliant, EN60950-1 EN12100-1, EN ISO13849-1, EN60204-1, and EN1010-1); Russia, Belarus and Kazakhstan (EAC); Australia, New Zealand (RCM)
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM)
Environmental	WEEE; RoHS (EU, China, Korea, Singapore, Turkey, Ukraine); India Waste Management Rules; REACH; CA 65 Prop; ErP Ecodesign Directive
Warranty	180-day limited hardware warranty. Warranty may vary by country as required by law. Go to http://www.hp.com/support to learn about HP service and support options in your region.

Ordering information

HP Latex R1000 Printer

Product K0Q47A

Accessories		
D9Z41B L5E74C T7V20A T7V21A Y6V16A	HP Large Format Onyx Thrive RIP Software HP Large Format Caldera Grand RIP Software HP Latex R1000 Roll Printing Kit HP Latex R1000 Extension Tables HP Latex R Series Edge Holders Kit	

Original HP printing supplies

G0Z00A G0Z01A	HP 886 Latex Printhead Cleaning Kit HP 872 3-liter Cyan Latex Ink Cartridge	
G0Z02A	HP 872 3-liter Magenta Latex Ink Cartridge	
G0Z03A	HP 872 3-liter Yellow Latex Ink Cartridge	
G0Z04A	HP 872 3-liter Black Latex Ink Cartridge	
G0Z05A	HP 872 3-liter Light Cyan Latex Ink Cartridge	
G0Z06A	HP 872 3-liter Light Magenta Latex Ink Cartridge	
G0Z07A	HP 872 3-liter Optimizer Latex Ink Cartridge	
G0Z08A	HP 872 3-liter Overcoat Latex Ink Cartridge	
G0Z09A	HP 886 3-liter White Latex Ink Cartridge	
G0Z21A	HP 886 White Latex Printhead	
G0Z22A	HP 886 Optimizer Latex Printhead	
G0Z24A	HP 886 Latex Printhead	

Original HP large format printing materials

HP Premium Removable Gloss Adhesive Vinyl HP Permanent Gloss Adhesive Vinyl HP Durable Backlit Fabric (Take-back program)⁴ HP Backlit Polyester Film (Take-back program)⁴

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

4BS24A/K0Q45-67270 HP Latex R Series Cleaning Kit 2WM39A/K0Q45-67267 HP Latex R Series Uptime Kit 2WM40A/K0Q45-67269 HP Latex R Series Expert Kit 2WP87A/K0Q45-67268 HP Latex R Series Reseller Kit K0Q45-67272 HP Latex R Series Service Maintenance Kit K0Q45-67273 HP Latex R Series White Service Maintenance Kit

ECO highlights

- Better for print operations—no hazard warning labels or HAPs, no special ventilation
- Better for the environment—HP designs end-to-end sustainability into large-format printing
 Water-based inks produce odorless prints²
- HP Latex Inks are UL ECOLOGO® and UL GREENGUARD GOLD Certified³

Please recycle large-format printing hardware and printing supplies. Find out how at our website: http://www.hp.com/ecosolutions

¹ Contains no Hazardous Air Pollutants according to EPA Method 311. Special ventilation equipment (air filtration) is not required to meet U.S. OSHA requirements. Special ventilation equipment installation is at the discretion of the customer—see the Site Preparation Guide for details. Customers should consult state and local requirements and regulations. Contains no Hazardous Air Pollutants according to EPA Method 311.

² There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

³ UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see http://www.ul.com/EL). UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL'S GREENGUARD Standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.ul.com/gg or http:/

¹ Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.
² Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. Backlit substrates measured in transmission mode may yield different results.
³ Roll media is only compatible with the purchase of the optional HP Latex R1000 Roll Printing KH

Kit.

A Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the HP Large Format Media take-back program. Programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.









