


Dispensing Instructions

- 1. Select the frame.** The frame should accommodate a minimum 13mm fitting height to the bottom of the eyewire and 10mm to the top. Adjust the frame for comfort and accuracy before taking measurements. Adjustable nose pads are recommended. Set the pantoscopic angle to 10-12°. Frame should have a slight face form.
- 2. PD and Fitting Height.** Measure monocular fitting height by marking each demo lens at the pupil centers with a felt tip pen. Measure monocular PD using a pupillometer or by using the fitting height marks. To translate lens markings into measurements, place the frame on the center of the triangle, ensuring the marks on the lens are on the zero (0) line. Using the chart, record the monocular PD and monocular vertical heights.
- 3. Frame verification.** Line up the pupillary mark on the demo lens with the cross on the chart. Verify that the distance and near zones are within the blue circle and that the eyewire is within the cutout diameter. This will ensure the minimum fitting height and cutout specifications are met. Confirm that the lens cutout is compatible with the material type you are specifying.
- 4. Include this information.** Make sure you include the following information in your lab order:
 - Monocular PD measurements
 - Monocular fitting height measurements
 - Manually traced right eyewire drawing
 - Frame A, B, ED, and DBL dimensions
 - Frame brand, model, and eyesize

If you are ordering KODAK Unique HD Lens, please also include the following additional measurements:

- Pantoscopic Tilt
- Refracted Vertex Distance
- Back Vertex Distance
- Wrap Angle
- Reading Distance




Note: The KODAK Unique Lens design cannot be applied unless items "a" through "d" in step 4 are provided. Full customization of KODAK Unique HD Lenses requires items "f" through "j". Default measurements for items "f" through "j" will be used if not provided.


- 5. Dispensing.** Confirm the monocular PD and fitting height. Confirm the fit on the patient by verifying that the fitting cross is properly positioned over the pupil. Adjust the frame as necessary.
- 6. Teach proper viewing.** Demonstrate the different viewing areas and appropriate head and eye movement.

IMPORTANT If an entire plus powers lens is within the yellow area, it may be too small to be surfaced to the desired minimum thickness and after edging, it could have thick edges. You may wish to recommend a different frame.

Frame Verification Chart (LEFT)



Frame Verification Chart (RIGHT)



Kodak Unique HD Lens

Kodak Unique Lens

Progressive Lens Dispensing Guide



WE ARE ALL UNIQUE.

Find out about KODAK Lens IDS - specially designed to acquire the necessary measurements for KODAK Unique HD Lenses:
www.signetarmorlite.com/KODAKLensIDS

Signet Armorlite, Inc.
 800-759-0075 • www.signetarmorlite.com
www.signetek.com



The Kodak trademark and trade dress are used under license from Kodak by Signet Armorlite, Inc. Unique HD is a trademark of Signet Armorlite, Inc. All other brands mentioned are the property of their respective owners. © 2015 Signet Armorlite, Inc. PN 877-650

- KODAK Unique Lens and KODAK Unique HD Lens offer:
- More than 50 material options
 - Six corridor lengths: 13mm - 18mm
 - Optional Rx prism

Kodak Unique Lens

KODAK Unique Lens is a digitally-created full backside progressive lens designed for the lens wearer who desires quick adaptation and exceptional performance.

Kodak Unique HD Lens

KODAK Unique HD Lens begins with the KODAK Unique Lens design and adds point-of-wear measurements for a more customized wearing experience.



	Lens Material All KODAK Unique and Unique HD Lenses include two-sided, scratch-resistant coating.	Colors	Sphere Range	Cylinder Range to -4.00, limited to a combined sph/cyl power of:	Maximum Cutout	Index of Refraction	Abbe Value	Specific Gravity (gm/cm ³)
Standard Index	Standard Resin		+4.00 to -8.00	-8.00	71mm	1.50	58	1.32
	* Trivex®		+4.50 to -10.00	-10.00	65mm	1.53	44	1.11
Thinner, Lighter Lenses	* Polycarbonate		+5.00 to -10.00	-10.00	71mm	1.586	30	1.20
	* 1.60 Index		+6.00 to -11.00	-11.00	60/65/70mm	1.596	38	1.31
	* 1.67 High Index		+10.00 to -12.00	-12.00	71mm	1.668	31	1.37
	1.74 High Index		+10.00 to -13.25	-13.25	70mm	1.738	33	1.47
Photochromic	Transitions® Signature™ VII 1.50	Gray/Brown/Green	+4.00 to -8.00	-8.00	68/72mm	1.497	60	1.27
	* Transitions Signature VII Trivex	Gray/Brown	+4.50 to -10.00	-10.00	73mm	1.53	44	1.11
	* Transitions Signature VII Polycarbonate	Gray/Brown/Green	+5.00 to -10.00	-10.00	69/74mm	1.586	31	1.20
	* Transitions Signature VII 1.60	Gray/Brown	+6.00 to -10.00	-10.00	71/75mm	1.596	41	1.30
	* Transitions Signature VII 1.67	Gray/Brown/Green	+6.00 to -11.00	-11.00	75/76mm	1.660	32	1.35
	Transitions Signature VII 1.74	Gray/Brown	+9.00 to -13.00	-13.00	75mm	1.730	31	1.46
	Transitions XTRActive™ 1.50	Gray	+4.50 to -8.00	-8.00	71mm	1.497	60	1.27
	* Transitions XTRActive Trivex	Gray	+5.00 to -10.00	-10.00	70mm	1.53	45	1.11
	* Transitions XTRActive Poly	Gray	+5.00 to -10.00	-10.00	69/74mm	1.586	30	1.20
	* Transitions XTRActive 1.67	Gray	+6.00 to -12.00	-12.00	75/76mm	1.660	32	1.36
	Transitions Vantage™ 1.50	Gray	+4.00 to -8.00	-8.00	71mm	1.497	60	1.27
	* Transitions Vantage Trivex	Gray	+4.50 to -10.00	-10.00	65mm	1.53	43	1.11
	* Transitions Vantage Poly	Gray	+5.00 to -10.00	-10.00	69/74mm	1.586	31	1.20
	PhotoViews™ 1.50	Gray/Brown	+4.00 to -8.00	-8.00	71mm	1.497	60	1.27
* PhotoViews Poly	Gray	+5.00 to -10.00	-10.00	69/74mm	1.586	31	1.20	
KODAK Sun Lenses								
Photochromic Polarized	NXT® Photochromic Polarized	Gray/Brown	+5.00 to -7.00	-7.00	70mm	1.53	45	1.11
	Drivewear® Standard Resin		+4.00 to -8.00	-8.00	69mm	1.50	58	1.30
Photochromic	* NXT Photochromic	Gray/Brown/Amber DayNite	+5.00 to -9.00	-9.00	70/75mm	1.53	45	1.11
Polarized	Polarized 1.50	Gray/Brown	+4.00 to -8.00	-8.00	75mm	1.499	58	1.32
	Polarized Trivex	Gray/Brown	+5.00 to -7.00	-7.00	70mm	1.53	45	1.11
	* Polarized Polycarbonate	Gray/Brown	+5.00 to -10.00	-10.00	70mm	1.586	28	1.20
	* Polarized 1.60	Gray/Brown	+5.75 to -10.00	-10.00	70mm	1.60	42	1.30
	* Polarized 1.67	Gray/Brown/Green	+10.00 to -12.00	-12.00	70/75mm	1.668	32	1.37
	Polarized 1.74	Gray/Brown/Green	+10.00 to -12.00	-12.00	70/75mm	1.738	32	1.47
Mirror	* NXT Mirror	Silver/Gold	+5.00 to -9.00	-9.00	70/75mm	1.53	45	1.11
Fixed Tint	* NXT Fixed Tint	Gray/Brown/Green	+5.00 to -9.00	-9.00	70/75mm	1.53	45	1.11
Specialty Lens	* BluTech™ Hi Impact 1.56 (Indoor)	Brown 0	+5.00 to -10.00	-10.00	70mm	1.556	46	1.25
	* BluTech Hi Impact 1.56 (Outdoor)	Brown 3	+5.00 to -8.00	-8.00	72mm	1.556	46	1.25

*Recommended for drill mount frames. NXT Lenses are made using Trivex.