



HP Latex R1000 Printer

Help grow your business with easy, automatic printing of high-value rigid jobs, and white¹



Get amazing colors for rigid jobs up to 64 inches

- Grow your business into higher value rigid jobs with vibrant HP Latex gamut, preserving media look and feel.
- Gain versatility with HP Latex Ink—from indoor/outdoor signage to thermoforming and high-quality decoration.
- Win more jobs with UL ECOLOGO® Certified, water-based HP Latex Inks that produce odorless prints.²

We've removed the barriers to print with white¹

- Be creative on a wide range of applications with glossiest white that resists yellowing over time.¹
- No waste between white jobs³ with removable HP Thermal Inkjet printheads stored in offline rotating chamber.
- You're always ready to print white—automatic recirculation and printhead cleaning eliminate manual purging.

Manage your peaks in-house with smart printing

- Get high-speed quality in all print modes—print up to 15 outdoor bds/hr with belt system and smart vacuum.⁴
- Help avoid costly operating mistakes with an easy interface, including assisted loading and advanced queuing.
- Maximize uptime with automatic maintenance and smart service tools for fast diagnosis and issue resolution.

For more information, please visit <http://www.hp.com/go/LatexRseries>

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at <https://hplatexknowledgecenter.com/>

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: <http://www.hp.com/go/learnaboutsupplies>

¹ Glossiest white based on internal HP testing in January, 2018 compared to the HP Scitex FB750/FB550 Printer using UV-curable ink technology. White ink measured for the level of gloss at 60 degrees on a rigid material (acrylic). Tested using Glossmeter BYK micro-TRI-gloss (20°, 60°, 85°), compatible with ISO 2813 and ASTM D523 relative to glossiness measure. High opacity and resists yellowing over time based on internal HP WeatherOmeter testing October, 2017 with 1 dot-per-pixel HP Latex Overcoat, on a range of rigid and flexible unlaminated substrates. Yellowing based on L* and B* of white underfloor samples.
² HP Latex Inks are UL ECOLOGO® Certified. UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see <http://www.ul.com/EL>). There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.
³ When HP 886 White Latex Printheads are placed in the storage cassettes, no white ink is used for servicing when printheads are not in use.
⁴ Outdoor mode 3-pass, 70%. On 4 x 8 ft (1.2 x 2.4 m) boards.

Technical specifications

Print

Printing modes	161 ft ² /hr (15 m ² /hr) - Indoor High Quality (12p 120%) 301 ft ² /hr (28 m ² /hr) - Indoor Production (6p 110%) 603 ft ² /hr (56 m ² /hr) - Outdoor (3p 70%) 269 ft ² /hr (25 m ² /hr) - White Spot (100%) 118 ft ² /hr (11 m ² /hr) - White Overflow (100%) 39 ft ² /hr (3.6 m ² /hr) - 3 layers day & night ¹
Print resolution	Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex Inks
Ink cartridges	9 (cyan, magenta, yellow, black, light cyan, light magenta, HP Latex Optimizer, HP Latex Overcoat, white)
Cartridge size	3 L
Printheads	8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 HP Latex Optimizer, 2 white)
Long-term print-to-print repeatability	Average \leq 1.0 dE2000, 95% of colors \leq 2 dE2000 ²

Media

Handling	Flatbed, sheet feed, vacuum belt media drive for easy loading and accurate media advance
Media types	Rigid substrates: paper foamboard, plastic foamboard, PVC foam, plastic corrugated, acrylic, polycarbonate, polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates ³ : PVC banner, self-adhesive vinyl, coated paper, polypropylene, polystyrene, polycarbonate, polyester, textile (non porous), canvas, leather
Rigid media size	11.7 x 16.5 in to 64 x 48 in (297 x 420 mm to 1625 x 1220 mm) Up to 64 x 120 in (1625 x 3050 mm) with two sets of optional extension tables
Thickness	Up to 2 in (Up to 50.8 mm)

Applications	Signage: indoor, flat, backlit, thermoformed; Decoration: wall coverings, window decoration; Vehicle decoration: fleet graphics, wraps, decals; Textile: soft signage, frontlit, backlit; POS and Packaging: corrugated displays, short-run customized packaging, prototyping
--------------	---

Connectivity

Interfaces	Gigabit Ethernet (1000Base-T)
------------	-------------------------------

Dimensions (w x d x h)

Printer	166 x 80 x 69 in (4.21 x 2.04 x 1.75 m) printer; 166 x 143 x 69 in (4.21 x 3.64 x 1.75 m) including standard input and output tables
Shipping	174 x 88 x 85 in (4.43 x 2.24 x 2.15 m)
Operating area	21.7 x 19.8 x 9.8 ft (6.61 x 6.03 x 3 m)

Weight

Printer	2811 lb (1275 kg)
Shipping	5016 lb (2275 kg)

What's in the box	HP Latex R1000 Printer; HP 886 Latex Printheads; HP Latex Printhead Cleaning Kit; standard input and output tables; foot switch; HP Internal Print Server and displays (x2); printer maintenance kit; warranty and intro docs
-------------------	---

Environmental ranges

Operating temperature	59 to 86°F (15 to 30°C)
Operating humidity	20 to 70% RH (non-condensing)

Power

Consumption	8 to 10 kW (typical)
-------------	----------------------

Certification

Safety	IEC 60950-1+A1+A2 compliant; United States and Canada (CSA listed)
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES)
Environmental	WEEE; REACH; CA 65 Prop; ErP Ecodesign Directive

Warranty	One-year Maintenance and Support covers: 180-day limited hardware warranty; six-month HP Standard Service, Maintenance and Support. Warranty may vary by country as required by law. Go to http://www.hp.com/support to learn about HP service and support options in your region.
----------	--

Ordering information

Product

K0Q47A	HP Latex R1000 Printer
--------	------------------------

Accessories

D9Z41B	HP Large Format Onyx Thrive RIP Software
T7V20A	HP Latex R1000 Roll Printing Kit
T7V21A	HP Latex R1000 Extension Tables
Y6V16A	HP Latex R Series Edge Holders Kit

Original HP printing supplies

GOZ00A	HP 886 Latex Printhead Cleaning Kit
GOZ01A	HP 872 3-liter Cyan Latex Ink Cartridge
GOZ02A	HP 872 3-liter Magenta Latex Ink Cartridge
GOZ03A	HP 872 3-liter Yellow Latex Ink Cartridge
GOZ04A	HP 872 3-liter Black Latex Ink Cartridge
GOZ05A	HP 872 3-liter Light Cyan Latex Ink Cartridge
GOZ06A	HP 872 3-liter Light Magenta Latex Ink Cartridge
GOZ07A	HP 872 3-liter Optimizer Latex Ink Cartridge
GOZ08A	HP 872 3-liter Overcoat Latex Ink Cartridge
GOZ09A	HP 886 3-liter White Latex Ink Cartridge
GOZ21A	HP 886 White Latex Printhead
GOZ22A	HP 886 Optimizer Latex Printhead
GOZ24A	HP 886 Latex Printhead

Original HP large format printing materials

HP Premium Removable Gloss Adhesive Vinyl
HP Permanent Gloss Adhesive Vinyl
HP Durable Backlit Fabric (Take-back program) ⁴
HP Backlit Polyester Film (Take-back program) ⁴

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

If you want to extend the support beyond what's included: H0HX4AC HP Standard Service, Maintenance and Support extension contract H0JR1AC HP Enhanced Service, Maintenance and Support extension contract UA5W05 HP Latex R series Level 3 Train to repair and maintain – 5 days training at HP UA3Q7E 3 Years Next Business Day with Defective Media Retention for HP Latex R1000 Plus K0Q45-67269 HP Latex R series Expert spare parts uptime kit

ECO highlights

- Better for print operations—no hazard warning labels or HAPs, no special ventilation needed¹
- Better for the environment—HP designs end-to-end sustainability into large-format printing
- Water-based inks produce odorless prints²
- HP Latex Inks are UL ECOLOGO® and UL GREENGUARD GOLD Certified³

Please recycle large-format printing hardware and printing supplies. Find out how at our website: <http://www.hp.com/ecosolutions>

¹ Contains no Hazardous Air Pollutants according to EPA Method 311. Special ventilation equipment (air filtration) is not required to meet U.S. OSHA requirements. Special ventilation equipment installation is at the discretion of the customer—see the Site Preparation Guide for details. Customers should consult state and local requirements and regulations. Contains no Hazardous Air Pollutants according to EPA Method 311.

² There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

³ UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see <http://www.ul.com/EL>). UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit <http://www.ul.com/gg> or <http://www.greenguard.org>.

¹ Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.

² Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard (IEDE2000 as per CIE Draft Standard DS 014-6/E:2012. Backlit substrates measured in transmission mode may yield different results.

³ Roll media is only compatible with the purchase of the optional HP Latex R1000 Roll Printing Kit.

⁴ Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the HP Large Format Media take-back program. Programs may not exist in your area. See <http://www.HPLFMedia.com/hp/ecosolutions> for details.

